

How to make X listen on port 6000

http://gentoo.linuxhowtos.org/bash/setting_command_aliases.pdf

[jump to the content](#)

Gentoo.LinuxHowtos.org howtos, tips&tricks and tutorials for gentoo linux

from small one page howto to huge articles all in one place

Other .linuxhowtos.org sites:
toolsntoys.linuxhowtos.org
forums.linuxhowtos.org

www.linuxhowtos.org

How to make X listen on port 6000

http://gentoo.linuxhowtos.org/bash/setting_command_aliases.pdf

Last additions:

How to make X listen on port 6000

How to make X listen on port 6000

words:

34

views:

4136

userrating:

May, 25th 2007:

Words

496

why adblockers are bad

April, 26th 2007:

Words

77

Website translation planned

Apr, 10th. 2007:

Words

63

Compile Time Estimator integrated into genlop

image:Druckversion

.
image:pdf icon

You are here:

(from gentoo-wiki.com)

The alias command allows you to make new shortcuts and synonyms for commonly used comands. The basic usage is:

```
alias newcommand='yourcommand -arguments'
```

If you want to start aterm according to your preferences with the command term, do something like:

```
alias term='aterm -ls -fg gray -bg black'
```

If you want a quick alias like ll for a more informative file listing:

```
ls -al --color=yes
```

Starting alias without any options lists the current aliases:

```
alias
```

```
alias ls='ll'  
alias ls -al --color=yes  
alias term='aterm -ls -fg gray -bg black'
```

Use `unalias` to remove an alias.

```
unalias term
```

You can also make aliases for existing commands. If you want `ls` to show colors by default, do:

```
alias ls='ls --color=yes'
```

These aliases can be put in your login script (`.bash_profile` or `.profile` depending on what shell you are using).

Alias with variables

You can not make aliases with variables. But you can make functions, having a function in your `.profile/.bashrc` will work just like an alias. To use `ssh` to copy files to a location on a server you can use

```
sendpic () { scp "$@" mina@foo.bar.ca:/www/misc/Pictures/; }
```

[edit]

Another way for aliases with variables

If you don't like to use a function, if you need variables, try the following to change to the last working directory:

```
alias cdo="cd \"\${OLDPWD}\""
```

Note: it is important, that there are ONLY double quotes in the expression above, no single quotes like in the other examples!

[edit]

Creating aliases on shell startup

How to make X listen on port 6000

http://gentoo.linuxhowtos.org/bash/setting_command_aliases.pdf

You can have your aliases created anytime you open an instance of a shell. If you are using bash, edit your `~/.bashrc` file and add one alias per line. Once you save and close the file, run this to load your new aliases immediately:

```
source ~/.bashrc
```

Otherwise, the new aliases will load whenever you open a new instance of the shell. Another place to put your aliases if you want them to be system-wide for all users is in `/etc/bashrc`. To load those aliases, add this line to `~/.bashrc`

```
source /etc/bashrc
```

current rating:

Please read "Why adblockers are bad".

<div id="wikilogin" title="Edits you make while logged in will be assigned to that name. That means you get full credit for your contributions in the page history (when not logged in, the edits are just assigned to Anonymous.)">

```
var google_ad_client = "pub-4309123515655559"; var  
google_alternate_color = "CCCCCC"; var google_ad_width = 160; var google_ad_height =  
600; var google_ad_format = "160x600_as"; var google_ad_channel = "3097575257"; var  
google_color_border = "000000"; var google_color_text = "000000"; var google_color_bg =  
"CCCCCC"; var google_color_link = "0000FF"; var google_color_url = "008000";
```

other Ads

Stellenangebote

Stellenangebote

für Fach- und

Führungskräfte

www.nachoben.com

Trace My Cash

Wenn Sie sich schon immer mal gefragt haben, wo eigentlich Ihr geliebtes Bargeld geblieben ist, finden Sie hier vielleicht die Antwort.

www.tracemycash.com

Other free services

toURL.org

Shorten long

URLs to short

links like

<http://turl.org/2>
turl.org

.

FeedCollector

Combine various newsfeeds to one customized webpage
www.feedcollector.org

.

Reverse DNS lookup

Find out which hostname(s)
resolve to a
given IP or other hostnames for the server
www.reversednslookup.org

New Packages

- as

image:rdf newsfeed

- as

image:rss newsfeed

- as

image:Atom newsfeed

image:rdf newsfeed

|

image:rss newsfeed

|

image:Atom newsfeed

- Powered by

image:LeopardCMS

- Running on

image:Gentoo

-

Copyright 2004 S&P Softwaredesign

image:Valid XHTML1.1

How to make X listen on port 6000

http://gentoo.linuxhowtos.org/bash/setting_command_aliases.pdf

:
image:Valid CSS
:
image:buttonmaker
- Level Triple-A Conformance to Web Content Accessibility Guidelines 1.0 -
- Copyright and legal notices -
Time to create this page: ms

image:system status display

Stellenangebote
bodyloaded(); document.getElementById("fulltextsearch").onkeypress=chk;
Ärger mit Freenet.de