

How to make X listen on port 6000

<http://gentoo.linuxhowtos.org/faq/missinglibstdc.pdf>

[jump to the content](#)

Gentoo.LinuxHowtos.org howtos, tips&tricks and tutorials for gentoo linux

from small one page howto to huge articles all in one place

Other .linuxhowtos.org sites:
toolsntoys.linuxhowtos.org

www.linuxhowtos.org

Last additions:

How to make X listen on port 6000

How to make X listen on port 6000

words:

34

views:

57581

userrating:

May, 25th 2007:

Words

496

why adblockers are bad

April, 26th 2007:

Words

77

Website translation planned

Apr, 10th. 2007:

Words

63

Compile Time Estimator integrated into genlop

image:Druckversion / /data/printer.gif (null)

image:pdf icon / /data/pdf.png (null)

You are here:

During emerge you get the error message libstdc++.la is missing?

Fix/Answer

run `fix_libtool_files.sh`

the old gcc version can be seen in the error message of the compiler line.
After a few seconds (or minutes) your libtool files are fixed.

Description:

During your gcc update there have been a few (sometimes dozen) libtool files left with the gcc path hardcoded in them. When you compile a program that uses those libtool files, the path is wrong and you get your missing libstdc++ error message.

From the `fix_libtool_files.sh` help:

```
Usage: fix_libtool_files.sh [--oldarch ]
```

```
Where is the version number of the
previous gcc version. For example, if you updated to
gcc-3.2.1, and you had gcc-3.2 installed, run:
```

```
# fix_libtool_files.sh 3.2
```

```
If you updated to gcc-3.2.3, and the old CHOST was i586-pc-linux-gnu
but you now have CHOST as i686-pc-linux-gnu, run:
```

```
# fix_libtool_files.sh 3.2 --oldarch i586-pc-linux-gnu
```

```
Note that if only the CHOST and not the version changed, you can run
it with the current version and the '--oldarch ' arguments,
and it will do the expected:
```

```
# fix_libtool_files.sh `gcc -dumpversion` --oldarch i586-pc-linux-gnu
```

current rating:

image:Support us on Content Nation //images/cn.png (null)

<!--

Other free services

toURL.org

Shorten long

URLs to short

How to make X listen on port 6000

<http://gentoo.linuxhowtos.org/faq/missinglibstdc.pdf>

links like

<http://turl.org/2>
turl.org

.

Reverse DNS lookup

Find out which hostname(s)

resolve to a

given IP or other hostnames for the server

www.reversednslookup.org

-->

New Packages

- as

image:rdf newsfeed //data/rdf.png (null)

- as

image:rss newsfeed //data/rss.png (null)

- as

image:Atom newsfeed //data/atom.png (null)

image:rdf newsfeed //data/rdf.png (null)

|

image:rss newsfeed //data/rss.png (null)

|

image:Atom newsfeed //data/atom.png (null)

- Powered by

image:LeopardCMS //data/leopardcms.png (null)

- Running on

image:Gentoo //data/gentoo.png (null)

-

Copyright 2004-2020 Sascha Nitsch Unternehmensberatung GmbH

image:Valid XHTML1.1 //data/xhtml.png (null)

:

image:Valid CSS //data/css.png (null)

:

image:buttonmaker //data/buttonmaker.png (null)

- Level Triple-A Conformance to Web Content Accessibility Guidelines 1.0 -

- Copyright and legal notices -

How to make X listen on port 6000

<http://gentoo.linuxhowtos.org/faq/missinglibstdc.pdf>

Time to create this page: ms

<!--

image:system status display / /status/output.jpg (null)

-->

bodyloaded();