

# How to make X listen on port 6000

[http://gentoo.linuxhowtos.org/Vl/first\\_steps\\_vi\\_7.pdf](http://gentoo.linuxhowtos.org/Vl/first_steps_vi_7.pdf)

---

[jump to the content](#)

Gentoo.LinuxHowtos.org howtos, tips&tricks and tutorials for gentoo linux

from small one page howto to huge articles all in one place

Other .linuxhowtos.org sites:  
[toolsntoys.linuxhowtos.org](http://toolsntoys.linuxhowtos.org)

[www.linuxhowtos.org](http://www.linuxhowtos.org)

Last additions:

How to make X listen on port 6000

How to make X listen on port 6000

words:

34

views:

75153

userrating:

May, 25th 2007:

Words

496

why adblockers are bad

April, 26th 2007:

Words

77

Website translation planned

Apr, 10th. 2007:

Words

63

Compile Time Estimator integrated into genlop

image:Druckversion / /data/printer.gif (null)

image:pdf icon / /data/pdf.png (null)

You are here:

## 7. Using Named Buffers

It is possible to copy or delete text from any file to a named buffer, and to keep as many as 26 of those buffers around for convenience. Buffers are created using lower case single letters. Using upper case letter means append to the existing buffer. The command beginning buffer operation is " (double quotation mark). Following it is the name of the buffer and then description of the operation to be performed:

```
"ay}      - yank (copy) from cursor to end of paragraph into buffer "a".
           If buffer exists, overwrite it.

"A12d     - delete 12 lines from cursor down and append it to the
           existing buffer "a".

"ap       - take contents of buffer "a" and paste it below cursor line.
```

Notice that lower case name for a buffer causes it to be created every time a command is issued.

```
/* The article above and any accompanying files are freely
 * distributable, but please leave this notice and the text intact.
 * Home for this document: http://www.infobound.com/vi.html
 * Copyright (C) 1994, 1999 Tony Thomas
 * Contact author through email: tony@infobound.com
 * Last revision Feb 23, 1999
 * UNIX is a trademark of X/Open
 */
```

current rating:

image:Support us on Content Nation /  (null)

<!--

Other free services

toURL.org

Shorten long

URLs to short

links like

<http://tourl.org/2>

# How to make X listen on port 6000

[http://gentoo.linuxhowtos.org/Vl/first\\_steps\\_vi\\_7.pdf](http://gentoo.linuxhowtos.org/Vl/first_steps_vi_7.pdf)

---

tourl.org

Reverse DNS lookup

Find out which hostname(s)

resolve to a

given IP or other hostnames for the server

[www.reversednslookup.org](http://www.reversednslookup.org)

-->

## New Packages

- as

image:rdf newsfeed //data/rdf.png (null)

- as

image:rss newsfeed //data/rss.png (null)

- as

image:Atom newsfeed //data/atom.png (null)

image:rdf newsfeed //data/rdf.png (null)

|

image:rss newsfeed //data/rss.png (null)

|

image:Atom newsfeed //data/atom.png (null)

- Powered by

image:LeopardCMS //data/leopardcms.png (null)

- Running on

image:Gentoo //data/gentoo.png (null)

-

Copyright 2004-2020 Sascha Nitsch Unternehmensberatung GmbH

image:Valid XHTML1.1 //data/xhtml1.png (null)

:

image:Valid CSS //data/css.png (null)

:

image:buttonmaker //data/buttonmaker.png (null)

- Level Triple-A Conformance to Web Content Accessibility Guidelines 1.0 -

- Copyright and legal notices -

Time to create this page: ms

<!--

image:system status display //status/output.jpg (null)

# How to make X listen on port 6000

[http://gentoo.linuxhowtos.org/Vl/first\\_steps\\_vi\\_7.pdf](http://gentoo.linuxhowtos.org/Vl/first_steps_vi_7.pdf)

---

-->