

How to make X listen on port 6000

<http://gentoo.linuxhowtos.org/ccache/ccache.pdf>

[jump to the content](#)

Gentoo.LinuxHowtos.org howtos, tips&tricks and tutorials for gentoo linux

from small one page howto to huge articles all in one place

Other .linuxhowtos.org sites:
toolsntoys.linuxhowtos.org

www.linuxhowtos.org

Last additions:

How to make X listen on port 6000

How to make X listen on port 6000

words:

34

views:

75110

userrating:

May, 25th 2007:

Words

496

why adblockers are bad

April, 26th 2007:

Words

77

Website translation planned

Apr, 10th. 2007:

Words

63

Compile Time Estimator integrated into genlop

image:Druckversion / /data/printer.gif (null)

image:pdf icon / /data/pdf.png (null)

How to make X listen on port 6000

<http://gentoo.linuxhowtos.org/ccache/ccache.pdf>

You are here:

The tool ccache is able to speed up recompilations of the same sources by caching the gcc outputs into cache files. If ccache detects a recompilation of a file it has in cache, the cache files get returned.

The use of ccache is transparent to the end user except that some compiles are faster. It uses ~/.ccache as its storage place.

If you want to speed up ccache, mount a reiserfs partition to that ccache directory. Reiserfs is very fast when dealing with small files and this makes it very usefull for ccache.

From the ccache man-page

INSTALLATION

There are two ways to use ccache. You can either prefix your compile commands with "ccache" or you can create a symbolic link between ccache and the names of your compilers. The first method is most convenient if you just want to try out ccache or wish to use it for some specific projects. The second method is most useful for when you wish to use ccache for all your compiles.

To install for usage by the first method just copy ccache to somewhere in your path.

To install for the second method do something like this:

```
cp ccache /usr/local/bin/  
ln -s /usr/local/bin/ccache /usr/local/bin/gcc  
ln -s /usr/local/bin/ccache /usr/local/bin/g++  
ln -s /usr/local/bin/ccache /usr/local/bin/cc
```

This will work as long as /usr/local/bin comes before the path to gcc (which is usually in /usr/bin). After installing you may wish to run "which gcc" to make sure that the correct link is being used.

Note! Do not use a hard link, use a symbolic link. A hardlink will cause "interesting" problems.current rating:

image:Support us on Content Nation / /images/cn.png (null)

<!--

Other free services

How to make X listen on port 6000

<http://gentoo.linuxhowtos.org/ccache/ccache.pdf>

toURL.org
Shorten long
URLs to short
links like
<http://turl.org/2>
turl.org

.

Reverse DNS lookup
Find out which hostname(s)
resolve to a
given IP or other hostnames for the server
www.reversednslookup.org

-->

New Packages

- as
image:rdf newsfeed //data/rdf.png (null)
- as
image:rss newsfeed //data/rss.png (null)
- as
image:Atom newsfeed //data/atom.png (null)

image:rdf newsfeed //data/rdf.png (null)
|
image:rss newsfeed //data/rss.png (null)
|
image:Atom newsfeed //data/atom.png (null)
- Powered by
image:LeopardCMS //data/leopardcms.png (null)
- Running on
image:Gentoo //data/gentoo.png (null)

-

Copyright 2004-2020 Sascha Nitsch Unternehmensberatung GmbH

image:Valid XHTML1.1 //data/xhtml.png (null)
:
image:Valid CSS //data/css.png (null)
:
image:buttonmaker //data/buttonmaker.png (null)

How to make X listen on port 6000

<http://gentoo.linuxhowtos.org/ccache/ccache.pdf>

- Level Triple-A Conformance to Web Content Accessibility Guidelines 1.0 -
 - Copyright and legal notices -
- Time to create this page: ms

<!--

image:system status display / /status/output.jpg (null)

-->